


# GRYPHON™ | GFE4400 2D



## ADVANCED IMAGING TECHNOLOGY

Using advanced imaging technology, the Gryphon™ GFE4400 2D engine provides a compact and easy-to-use solution for OEM use in self-service kiosks, price verifiers, ticket readers, document handling and medical laboratory applications, as well as vending machines and other automated equipment.

The GFE4400 2D OEM engine features outstanding near-field reading, a wide angle field-of-view, high motion tolerance, snappy reading, and also offers excellent performance on decoding poor or damaged bar codes. The GFE4400 2D OEM engine also offers good-read visual confirmation with Datalogic's patented 'Green Spot' technology.

## RED ILLUMINATING LIGHT AND 4-DOT AIMER

User comfort is maximized with the GFE4400 2D OEM engine's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

## 1D AND 2D CAPABILITIES

The GFE4400 2D OEM engine provides snappy reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. For mobile marketing or ticketing applications, this imager also offers excellent performance when reading bar codes from mobile devices.

## FEATURES

- Highly visible 4-Dot aimer with center cross for targeted scanning
- Omnidirectional reading
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads bar codes down to 4 mils
- Reads 1D, 2D and postal codes plus stacked and composite codes
- Interface options: RS-232 or USB
- Datalogic's patented 'Green Spot' technology for good-read feedback
- Automatic sensing or manual trigger options available
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

## INDUSTRY-APPLICATIONS

- OEM Applications:
  - Service Kiosks
  - Price Verifiers
  - Ticket Readers
  - Document Handling
  - Medical Laboratories
  - Vending Machines
  - Additional Automated Equipment



# TECHNICAL SPECIFICATIONS

DECODING CAPABILITY	
<b>1D / Linear Codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
<b>2D Codes</b>	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code
<b>Postal Codes</b>	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
<b>Stacked Codes</b>	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

ELECTRICAL	
<b>Current</b>	Operating (Typical): < 180 mA Standby/Idle (Typical): Automatic Object Sense Mode: 115 mA Online & Serial OnLine Modes: 65 mA
<b>Input Voltage</b>	5 VDC +/- 5%

ENVIRONMENTAL	
<b>Ambient Light</b>	0 - 100,000 lux
<b>Humidity (Non-Condensing)</b>	5 - 95%
<b>Temperature</b>	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES	
<b>Interfaces</b>	OEM (IBM) USB; RS-232; USB: USB COM; USB HID Keyboard

PHYSICAL CHARACTERISTICS	
<b>Dimensions</b>	2.8 x 4.2 x 4.8 cm / 1.1 x 1.7 x 1.9 in
<b>Weight</b>	USB: 51.2 g / 1.8 oz RS-232: 51.2 g / 1.8 oz

READING PERFORMANCE	
<b>Image Capture</b>	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
<b>Image Sensor</b>	Wide VGA: 752 x 480 pixels
<b>Light Source</b>	Aiming: 650 nm VLD
<b>Print Contrast Ratio (Minimum)</b>	25%
<b>Reading Angle</b>	Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°
<b>Resolution (Maximum)</b>	1D Linear: 0.102 mm / 4 mils Data Matrix: 0.178 mm / 7 mils PDF417: 0.102 mm / 4 mils

READING RANGES	
<b>Typical Depth of Field</b>	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. Code 39: 5 mil: 4.7 to 17.7 cm / 1.8 to 7.0 in Code 39: 10 mil: 1.7 to 33.2 cm / 0.7 to 13.1 in Data Matrix: 10 mil: 2.7 to 17.1 cm / 1.0 to 6.7 in Data Matrix: 15 mil: 1.2 to 24.6 cm / 0.5 to 9.7 in EAN: 13 mil: 2.5 to 41.9 cm / 1.0 to 16.5 in PDF417: 10 mil: 2.2 to 23.9 cm / 0.9 to 9.4 in QR Code: 10 mil: 3.5 to 16.0 cm / 1.4 to 6.3 in

SAFETY & REGULATORY	
<b>Agency Approvals</b>	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
<b>Environmental Compliance</b>	Complies to China RoHS; Complies to EU RoHS
<b>Laser Classification</b>	Caution Laser Radiation - Do not stare into beam; IEC 60825, Class2

UTILITIES	
<b>Datalogic Aladdin™</b>	Datalogic Aladdin configuration program is available for download at no charge.
<b>OPOS / JavaPOS</b>	OPOS and JavaPOS utilities are available for download at no charge.
<b>Remote Host Download</b>	Lowers service costs and improves operations.

WARRANTY	
<b>Warranty</b>	18-Month Factory Warranty

