



T123F



SATO Ribbons | Value Wax | Wax Resin

- Premium Wax / Resin Formula
- Excellent Image Density & Durability
- Print Speeds up to 10 ips
- High Smudge & Scratch Resistance
- Prints on Coated Labels and Tags
- Prints at Low Print Head Energy Heat Settings
- Best Performance for Value Solution



Value Wax - Wax Resin Thermal Transfer Ribbon

RIBBON PROPERTY	
Base Material	Polyester Film
Ink Color	Black
Transmission Density	1.95
Back Coating	Yes
Total Thickness	7.1 ± 0.3 μm
Ink Thickness	2.8 ± 0.2 μm
Electrostatic	≤ 0.06 Kv
Optical Density	≥ 1.82 D
Ink Melt Point	154.4°F / 68°C
PRINTING PROPERTY	
Image Density	High
Recommended Substrates	Art paper, coated and uncoated paper, tag stocks, and vellums
DURABILITY OF PRINTED IMAGE	
Smudge Resistance	High
Scratch Resistance	High
Storage Condition	40°-90°F (5-35°C), 20-85% RH
Storage Life	1 Year after manufacturing

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

SATO AMERICA CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
sales-sallc@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com

©2018 SATO America. All rights Reserved. Rev A • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.